Appendix A: National and California Ambient Air Quality Standards							
C D C L 2040							

## **Ambient Air Quality Standards**

Pollutant	Averaging Time	California Standards 1		Federal Standards <sup>2</sup>		
Pollutant		Concentration <sup>3</sup>	Method <sup>4</sup>	Primary 3,5	Secondary <sup>3,6</sup>	Method 7
Ozone (O <sub>3</sub> )	1 Hour	0.09 ppm (180 µg/m³)	Ultraviolet		Same as Primary Standard	Ultraviolet Photometry
020110 (03)	8 Hour	0.070 ppm (137 μg/m³)	Photometry	0.075 ppm (147 μg/m³)		
Respirable Particulate	24 Hour	50 μg/m³	Gravimetric or	150 μg/m³	Same as Primary Standard	Inertial Separation and Gravimetric Analysis
Matter (PM10)	Annual Arithmetic Mean	20 μg/m³	Beta Attenuation	_		
Fine Particulate	24 Hour	No Separate St	tate Standard	35 μg/m³	Same as	Inertial Separation
Matter (PM2.5)	Annual Arithmetic Mean	12 μg/m <sup>3</sup>	Gravimetric or Beta Attenuation	15.0 μg/m <sup>3</sup> Primary Standard		and Gravimetric Analysis
Carbon	8 Hour	9.0 ppm (10mg/m <sup>3</sup> )	Non-Dispersive Infrared Photometry (NDIR)	9 ppm (10 mg/m³)	- None	Non-Dispersive Infrared Photometr (NDIR)
Monoxide	1 Hour	20 ppm (23 mg/m <sup>3</sup> )		35 ppm (40 mg/m <sup>3</sup> )		
(CO)	8 Hour (Lake Tahoe)	6 ppm (7 mg/m³)				-
Nitrogen Dioxide	Annual Arithmetic Mean	0.030 ppm (57 µg/m3)	Gas Phase Chemiluminescence	0.053 ppm (100 µg/m³)	Same as Primary Standard  None  Che	Gas Phase
(NO <sub>2</sub> )	1 Hour	0.18 ppm (339 µg/m³)		0.100 ppm (see footnote 8)		Chemil <mark>uminescen</mark> c
	Annual Arithmetic Mean		Ultraviolet Fluorescence	0.030 ppm (80 µg/m³)	<u>-</u>	Spectrophotometry (Pararosaniline Method)
Sulfur Dioxide	24 Hour	0.04 ppm (105 µg/m³)		0.14 ppm (365 μg/m³)		
(SO <sub>2</sub> )	3 Hour	_			0.5 ppm (1300 μg/m <sup>3</sup> )	
	1 Hour	0.25 ppm (655 μg/m³)				
	30 Day Average	1.5 µg/m³	Atomic Absorption		_	=
Lead <sup>9</sup>	Calendar Quarter	_		1.5 μg/m³	Same as	High Volume Sampler and Atomi Absorption
	Rolling 3-Month Average <sup>10</sup>	=		0.15 μg/m <sup>3</sup>	Primary Standard	
Visibility Reducing Particles  8 Hour  Extinction coefficient of 0.23 per kilometer — visibility of ten miles or more (0.07 — 30 miles or more for Lake Tahoe) due to particles when relative humidity is less than 70 percent. Method: Beta Attenuation and Transmittance through Filter Tape.		No				
Sulfates	24 Hour	25 μg/m³	Ion Chromatography	Federal		
Hydrogen Sulfide	1 Hour	0.03 ppm (42 μg/m³)	Ultraviolet Fluorescence	Standards		
Vinyl Chloride <sup>9</sup>	24 Hour	0.01 ppm (26 μg/m³)	Gas Chromatography			

- 1. California standards for ozone, carbon monoxide (except Lake Tahoe), sulfur dioxide (1 and 24 hour), nitrogen dioxide, suspended particulate matter—PM10, PM2.5, and visibility reducing particles, are values that are not to be exceeded. All others are not to be equaled or exceeded. California ambient air quality standards are listed in the Table of Standards in Section 70200 of Title 17 of the California Code of Regulations.
- 2. National standards (other than ozone, particulate matter, and those based on annual averages or annual arithmetic mean) are not to be exceeded more than once a year. The ozone standard is attained when the fourth highest eight hour concentration in a year, averaged over three years, is equal to or less than the standard. For PM10, the 24 hour standard is attained when the expected number of days per calender year with a 24-hour average concentration above  $150 \,\mu\text{g/m}^3$  is equal to or less than one. For PM2.5, the 24 hour standard is attained when 98 percent of the daily concentrations, averaged over three years, are equal to or less than the standard. Contact U.S. EPA for further clarification and current federal policies.
- 3. Concentration expressed first in units in which it was promulgated. Equivalent units given in parentheses are based upon a reference temperature of 25°C and a reference pressure of 760 torr. Most measurements of air quality are to be corrected to a reference temperature of 25°C and a reference pressure of 760 torr; ppm in this table refers to ppm by volume, or micromoles of pollutant per mole of gas.
- 4. Any equivalent procedure which can be shown to the satisfaction of the ARB to give equivalent results at or near the level of the air quality standard may be used.
- 5. National Primary Standards: The levels of air quality necessary, with an adequate margin of safety to protect the public health.
- 6. National Secondary Standards: The levels of air quality necessary to protect the public welfare from any known or anticipated adverse effects of a pollutant.
- 7. Reference method as described by the EPA. An "equivalent method" of measurement may be used but must have a "consistent relationship to the reference method" and must be approved by the EPA.
- 8. To attain this standard, the 3-year average of the 98th percentile of the daily maximum 1-hour average at each monitor within an area must not exceed 0.100 ppm (effective January 22, 2010).
- 9. The ARB has identified lead and vinyl chloride as 'toxic air contaminants' with no threshold level of exposure for adverse health effects determined. These actions allow for the implementation of control measures at levels below the ambient concentrations specified for these pollutants.
- 10. National lead standard, rolling 3-month average: final rule signed October 15, 2008.